



**The TecNiq P10** was built for the demanding task of illumination in the most extreme conditions. Comprised of anodized aluminum, impact resistant polycarbonate, 100% waterproof and vibration resistant - the P10 is a work horse. Proven performance with TecNiq proprietary thermal management testing and IP68 rated. Our flush mount work light beats the competition in quality and performance.



**P10** 


## FLUSH MOUNTED SPREADER LIGHT

## **Technical features**

- ☆ Reliable performance over 50,000 hours
- Proprietary thermal management provides powerful performance in a small package
- Designed for the most demanding task illumination applications, in the most extreme environments

## **Specifications**

Dimensions:	4.81"x 1.73"x 1.5"	
LEDs:	4 (white), or 2 + 2 red (red option)	
Voltage:	9 - 30VDC	
Connector:	9" Pigtail	
Mounting:	Flush mounted using two regular screws	
Lumens:	1300 Lumens, 700 Lumens +155 (red comb	



## California Proposition 65

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm

Part Numbers		Description	Std	Connector
	<u>P10-WRFP-1</u>	Spreader Light, White & Red LED, Flush Mount, White Finish, Pigtail Wires	2	Sheathed Pigtail 9"
	P10-WWFP-1	Spreader Light, White LED, Flush Mount, White Finish, Pigtail Wires	2	Sheatehd Pigtail 9"



PHONE: 269-629-4440 EMAIL: sales@tecniqinc.com WEB: www.TecNiqInc.com