

While narrow and thin, the **T12** meets FMVSS requirements with a wide angle of bright illumination for maximum safety. Unlike similar lamps, ours is TRULY vacuum sealed for a lifetime of care-free service. Made with top-quality materials, urethane potting and durable polycarbonate construction. **See www.TecNiqInc.com for more details and a complete list of part numbers.**

T12

Over 80" ID Bar



Technical features

- # Meets all FMVSS 108 requirements for wide and narrow vehicles
- ☆ Durable impact resistant lens
- \$\square\$ IP68 Rated for dust and water proof with hermetic seal
- # TecSeal Urethane Potting material guarantees circuit boards
- A Reliable performance over 100,000 hours
- \$\\$ ID Bar must be mounted horizontally

0.479"

Specifications

	←	15.521″
Dimensions	15.52" x 1.28" x 0.48" (see diagram)	
LED's	3	14.5"
Current	0.04A-0.07A Red / 0.04A-0.07A Amber 0.325A-0.395A Red/White Combo	
Connector	9" wire	
Mounting	Surface mount using (2) #8 screws (screw covers included)	
Voltage	9 - 14V DC	
LED Colors	Red, Amber, Red/White combo	
Wire Colors	White Wire Ground red/amber stripe	California Proposition 65

Ted/amber stripe

California Proposition 65

Black Wire ID Bar Function

WARNING: This product can exp

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm

1.281″

Part Numbers		Description	Std	Connector
	T10-0B00-1	Black Bezel	100	-
	T10-0C00-1	Chrome Bezel	100	-
	T12-RC00-1	Red Low Profile ID Bar Clear Lens	125	Pigtail
	T12-RR00-1	Red Low Profile ID Bar Red Lens	125	Pigtail



